

SECTION THROUGH CROSSING

NOTES:

- I. ALL DIMENSIONS ARE IN METRES UNLESS OTHERWISE SHOWN.
- 2. THE PROPERTY OWNER IS RESPONSIBLE FOR THE CONSTRUCTION AND MAINTENANCE OF THE DRIVEWAY AND CULVERT, INCLUDING THE LOCATION OF UNDERGROUND SERVICES WHICH MAY BE AFFECTED BY THE EXCAVATION.
- 3. THE PROPERTY OWNER IS RESPONSIBLE FOR OBTAINING A COUNCIL PERMIT FOR THE CONSTRUCTION.
- 4. VEHICLE CROSSING TO BE 50mm DEPTH CLASS 3 FINE CRUSHED ROCK.
- 5. MINIMUM COVER OVER PIPED CULVERT TO BE 150mm. SHOULD MINIMUM COVER BE UNACHIEVABLE, STRONGER CLASS PIPES TO THE SATISFACTION OF COUNCIL MUST BE INSTALLED.
- 6. DIAMETER OF PIPE CULVERT TO BE ADVISED BY COUNCIL WHEN VEHICLE CROSSING PERMIT ISSUED.
- 7. ALL CULVERTS TO BE CLASS 2 CONCRETE BUTT JOINT PIPES.
- 8. ALL SEALED ROAD PAVEMENTS MUST BE SAW-CUT ALONG THE EDGE OF PAVEMENT.
- 9. ALL WORKS MUST BE CARRIED OUT AND SITE REINSTATED TO THE SATISFACTION OF THE SUPERVISING OFFICER.
- 10. THE SITE SHALL BE MAINTAINED SAFE AT ALL TIMES IN ACCORDANCE WITH AS17423.
- 11. CONCRETE OR ASPHALT VEHICLE CROSSING WILL BE CONSIDERED ON APPLICATION. ALL WORKS TO BE CARRIED OUT WITH THE APPROVAL OF THE SUPERVISING OFFICER.

